



# AMERICAN BILTRITE

## AB-164

60 DURO SBR / PLATE FINISH / BLACK / TRIMMED / WITH POWDER

GAUGE	ITEM NUMBER 36"	ITEM NUMBER 48"
<b>SPECIFICATION: AA608A13</b>		
1/16"	<b>164-04-362 (S)</b>	<b>164-04-482 (S)</b>
1/8"	<b>164-08-362 (S)</b>	<b>164-08-482 (S)</b>
3/16"	164-12-362	<b>164-12-482 (S)</b>
1/4"	164-16-362	<b>164-16-482 (S)</b>
3/8"	164-24-362	<b>164-24-482 (S)</b>
1/2"	164-32-362	<b>164-32-482 (S)</b>
5/8"	164-40-362	164-40-482
3/4"	164-48-362	164-48-482
1"	164-64-362	164-64-482

(S) Normally available from inventory.

### STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. SQ. FT. PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	150'	125'	194 LBS.	215 LBS.	450 SQ. FT.	500 SQ. FT.
1/8"	.020	75'	65'	189 LBS.	218 LBS.	225 SQ. FT.	260 SQ. FT.
3/16"	.031	60'	45'	229 LBS.	229 LBS.	180 SQ. FT.	180 SQ. FT.
1/4"	.031	45'	35'	228 LBS.	237 LBS.	135 SQ. FT.	140 SQ. FT.
3/8"	.047	45'	35'	342 LBS.	354 LBS.	135 SQ. FT.	140 SQ. FT.
1/2"	.047	45'	35'	457 LBS.	473 LBS.	135 SQ. FT.	140 SQ. FT.
5/8"	.063	30'	30'	381 LBS.	508 LBS.	90 SQ. FT.	120 SQ. FT.
3/4"	.093	30'	30'	456 LBS.	608 LBS.	90 SQ. FT.	120 SQ. FT.
1"	.100	30'	25'	608 LBS.	676 LBS.	90 SQ. FT.	100 SQ. FT.

Maximum pieces per roll: 1/16" to 1/2" - 2 pieces, 5/8" to 1" - 1 piece

Minimum piece length: 10'

Width tolerance: +1"/-1/2"

Length tolerance: 1/16" to 1/2" +/-10%, 5/8" to 1" +10%, Min. 10'

#### Minimum Order:

Inventory Item: 1 Roll

Non-inventory Item: 2,000 lbs.

Custom Made Item: 3,000 lbs.

### AB-164 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	SBR/NR	
HARDNESS	60	SHORE "A" DUROMETER
TENSILE	800	PSI
ELONGATION	300	%

American Biltrite ISO 9001 manufactured product