



# AMERICAN BILTRITE

## AB-245

40 DURO NEOPRENE BLEND / INDUSTRIAL GRADE / PLATE FINISH / BLACK / MODERATE OIL RESISTANCE / TRIMMED / WITH PLASTIC LINER (NO POWDER)

GAUGE	ITEM NUMBER	ITEM NUMBER
	36"	48"
SPECIFICATION : BC410		
1/16"	244-04-362 (S)	244-04-482 (S)
3/32"	244-06-362	244-06-482
1/8"	244-08-362 (S)	244-08-482 (S)
3/16"	244-12-362 (S)	244-12-482 (S)
1/4"	244-16-362 (S)	244-16-482 (S)
3/8"	244-24-362	244-24-482 (S)
1/2"	244-32-362	244-32-482 (S)

(S) Normally available from inventory.

NOTE: Available with powder -- minimum quantities apply.

### STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. SQ. FT. PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	150'	125'	166 LBS.	184 LBS.	450 SQ. FT.	500 SQ. FT.
3/32"	.016	75'	65'	125 LBS.	145 LBS.	225 SQ. FT.	260 SQ. FT.
1/8"	.020	75'	65'	167 LBS.	193 LBS.	225 SQ. FT.	260 SQ. FT.
3/16"	.031	60'	45'	201 LBS.	201 LBS.	180 SQ. FT.	180 SQ. FT.
1/4"	.031	45'	35'	201 LBS.	208 LBS.	135 SQ. FT.	140 SQ. FT.
3/8"	.047	45'	35'	301 LBS.	312 LBS.	135 SQ. FT.	140 SQ. FT.
1/2"	.047	45'	35'	401 LBS.	416 LBS.	135 SQ. FT.	140 SQ. FT.

Maximum pieces per roll: 1/16" to 1/2" - 2 pieces

Minimum piece length: 10'

Width tolerance: +1"/-1/2"

Length tolerance: +/-10%

#### Minimum Order:

Inventory Item: 1 Roll

Non-inventory Item: 2,000 lbs.

Custom Made Item: 3,000 lbs.

### AB-245 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	CR/NBR/SBR	
HARDNESS	40	SHORE "A" DUROMETER
TENSILE	1250	PSI
ELONGATION	400	%
OIL AGING # 1 OIL	70 HOURS	100 ° C
CHANGED-HARDNESS	-6	POINTS
CHANGED-TENSILE	-24	%
CHANGED-ELONGATION	-27	%
CHANGED-MASS		%
CHANGED-VOLUME	5	%