



AMERICAN BILTRITE

AB-258

50 DURO NEOPRENE (98% CR BASE) / SUPREME GRADE / PLATE FINISH / BLACK / EXCELLENT OIL RESISTANCE / TRIMMED / WITH POWDER

GAUGE	ITEM NUMBER 36"	ITEM NUMBER 48"
SPECIFICATION : 2BC525A14B14C12E034		
1/16"	205-04-362	205-04-482
3/32"	205-06-362	205-06-482
1/8"	205-08-362	205-08-482
3/16"	205-12-362	205-12-482
1/4"	205-16-362	205-16-482
3/8"	205-24-362	205-24-482
1/2"	205-32-362	205-32-482

(S) Normally available from inventory.

STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. SQ. FT. PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	150'	125'	189 LBS.	210 LBS.	450 SQ. FT.	500 SQ. FT.
3/32"	.016	75'	65'	144 LBS.	166 LBS.	225 SQ. FT.	260 SQ. FT.
1/8"	.020	75'	65'	191 LBS.	221 LBS.	225 SQ. FT.	260 SQ. FT.
3/16"	.031	60'	45'	229 LBS.	229 LBS.	180 SQ. FT.	180 SQ. FT.
1/4"	.031	45'	35'	228 LBS.	237 LBS.	135 SQ. FT.	140 SQ. FT.
3/8"	.047	45'	35'	343 LBS.	356 LBS.	135 SQ. FT.	140 SQ. FT.
1/2"	.047	45'	35'	458 LBS.	475 LBS.	135 SQ. FT.	140 SQ. FT.

Maximum pieces per roll: 2
 Minimum piece length: 10'
 Width tolerance: +1"/-1/2"
 Length tolerance: +/-10%

Minimum Order:
 Inventory Item: 1 Roll
 Non-inventory Item: 2,000 lbs.
 Custom Made Item: 3,000 lbs.

AB-258 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	CR	
HARDNESS	50	SHORE "A" DUROMETER
TENSILE	2700	PSI
ELONGATION	500	%
OIL AGING # 3 OIL	70 HOURS	100 ° C
CHANGED-HARDNESS	-21	POINTS
CHANGED-TENSILE	-51	%
CHANGED-ELONGATION	-46	%
CHANGED-MASS	49	%
CHANGED-VOLUME	64	%