



AMERICAN BILTRITE

AB-268

60 DURO NEOPRENE (98% CR BASE) / SUPREME GRADE / PLATE FINISH / BLACK / EXCELLENT OIL RESISTANCE / TRIMMED / WITH POWDER

GAUGE	ITEM NUMBER 36"	ITEM NUMBER 48"
SPECIFICATION: 2BC625A14B14C12E034		
1/16"	206-04-362	206-04-482
3/32"	206-06-362	206-06-482
1/8"	206-08-362 (S)	206-08-482 (S)
3/16"	206-12-362	206-12-482
1/4"	206-16-362	206-16-482
3/8"	206-24-362	206-24-482
1/2"	206-32-362	206-32-482

(S) Normally available from inventory.

STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. WEIGHT PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	150'	125'	194 LBS.	215 LBS.	450 SQ. FT.	500 SQ. FT.
3/32"	.016	75'	65'	146 LBS.	169 LBS.	225 SQ. FT.	260 SQ. FT.
1/8"	.020	75'	65'	194 LBS.	224 LBS.	225 SQ. FT.	260 SQ. FT.
3/16"	.031	60'	45'	232 LBS.	232 LBS.	180 SQ. FT.	180 SQ. FT.
1/4"	.031	45'	35'	232 LBS.	241 LBS.	135 SQ. FT.	140 SQ. FT.
3/8"	.047	45'	35'	350 LBS.	363 LBS.	135 SQ. FT.	140 SQ. FT.
1/2"	.047	45'	35'	466 LBS.	483 LBS.	135 SQ. FT.	140 SQ. FT.

Maximum pieces per roll: 2

Minimum piece length: 10'

Width tolerance: +1"/-1/2"

Length tolerance: +/-10%

Minimum Order:

Inventory Item: 1 Roll

Non-inventory Item: 2,000 lbs.

Custom Made Item: 3,000 lbs.

AB-268 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	CR/BR	
HARDNESS	60	SHORE "A" DUROMETER
TENSILE	2900	PSI
ELONGATION	500	%
OIL AGING # 3 OIL	70 HOURS	100 ° C
CHANGED-HARDNESS	-24	POINTS
CHANGED-TENSILE	-68	%
CHANGED-ELONGATION	-54	%
CHANGED-MASS		%
CHANGED-VOLUME	69	%