



AMERICAN BILTRITE

AB-289

80 DURO NEOPRENE (55% CR BASE) / PREMIUM GRADE / SATIN FINISH /
VERY GOOD OIL RESISTANCE / UNTRIMMED / NO POWDER

| GAUGE | ITEM NUMBER 36" | ITEM NUMBER 48" |
|---|-----------------------|--------------------|
| SPECIFICATION: 2BC810B14C12A14EO34 | | |
| 1/16" | 283-04-362 (S) | 283-04-482 |
| 3/32" | 283-06-362 (S) | 283-06-482 |
| 1/8" | 283-08-362 (S) | 283-08-482 |
| 3/16" | 283-12-362 (S) | 283-12-482 |
| 1/4" | 283-16-362 | 283-16-482 |

(S) Normally available from inventory.

STANDARD DIMENSIONS

| GAUGE | TOLERANCE (+/-) | ROLL LENGTH | | APPROX. WEIGHT PER ROLL | | APPROX. SQ. FT. PER ROLL | |
|-------|--------------------|-------------|------|-------------------------|----------|--------------------------|-------------|
| | | 36" | 48" | 36" | 48" | 36" | 48" |
| 1/16" | .016 | 150' | 150' | 203 LBS. | 270 LBS. | 450 SQ. FT. | 600 SQ. FT. |
| 3/32" | .016 | 50' | 65' | 101 LBS. | 174 LBS. | 150 SQ. FT. | 260 SQ. FT. |
| 1/8" | .020 | 50' | 50' | 134 LBS. | 178 LBS. | 150 SQ. FT. | 200 SQ. FT. |
| 3/16" | .031 | 50' | 50' | 201 LBS. | 268 LBS. | 150 SQ. FT. | 200 SQ. FT. |
| 1/4" | .031 | 50' | 50' | 289 LBS. | 358 LBS. | 150 SQ. FT. | 200 SQ. FT. |

Maximum pices per roll: 2
Minimum piece length: 10'
Width tolerance: +1"/-1/2"
Length tolerance: +/-10%

Minimum Order:
Inventory Item: 1 Roll
Non-inventory Item: 2,000 lbs.
Custom Made Item: 3,000 lbs.

AB-289 PHYSICAL PROPERTIES

| DESCRIPTION | TYPICAL VALUE | UNITS |
|--------------------|---------------|---------------------|
| POLYMER | CR/SBR | |
| HARDNESS | 80 | SHORE "A" DUROMETER |
| TENSILE | 1000 | PSI |
| ELONGATION | 200 | % |
| OIL AGING # 3 OIL | 70 HOURS | 100 ° C |
| CHANGED-HARDNESS | -37 | POINTS |
| CHANGED-TENSILE | -43 | % |
| CHANGED-ELONGATION | -37 | % |
| CHANGED-MASS | 28 | % |
| CHANGED-VOLUME | 45 | % |