



AMERICAN BILTRITE

AB-3205

70 DURO NEOPRENE DIAPHRAGM SHEET WITH 9.5 OZ. POLYESTER FABRIC / PLATE FINISH / BLACK / TRIMMED / WITH POWDER

ITEM NUMBER	
48"	
SPECIFICATION: 2BC714A14B14EO14EO34	
1/16" -1 PLY	255-04-482 (S)
3/32" -1 PLY	255-06-482 (S)
1/8" -2 PLY	255-08-482 (S)
3/16" -3 PLY	255-12-482 (S)
1/4" -4 PLY	255-16-482 (S)

(S) Normally available from inventory.

STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH	APPROX. WEIGHT PER ROLL 48"	APPROX. SQ. FT. PER ROLL 48"
1/16" - 1 PLY	.016	100'	192 LBS.	400 SQ. FT.
3/32" - 1 PLY	.016	75'	225 LBS.	300 SQ. FT.
1/8" - 2 PLY	.020	50'	202 LBS.	200 SQ. FT.
3/16" - 3 PLY	.031	25'	150 LBS.	100 SQ. FT.
1/4" - 4 PLY	.031	25'	207 LBS.	100 SQ. FT.

Maximum pieces per roll: 2

Minimum piece length: 10'

Width tolerance: +1"/-1/2"

Length tolerance: +/-10%

Minimum Order:

Inventory Item: 1 Roll

Non-inventory Item: 2,000 lbs.

Custom Made Item: 3,000 lbs.

AB-3205 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	SBR/CR	
HARDNESS	70	SHORE "A" DUROMETER
TENSILE	1400	PSI
ELONGATION	230	%

American Biltrite ISO 9001 manufactured product